



| | |
|------------------------------------|---|
| Product Image | |
| Part number | 909020119 – PAC OneProx™ GS3 HF Panel Reader - yellow and black 909022119 – PAC OneProx™ GS3 HF Panel Reader - blue and grey |
| Dimensions | W 75 x H 80 x D 16mm |
| Weight | 90g |
| RFid Frequency | High Frequency (13.56MHz) |
| PAC ID Devices | PAC Ops™ Lite and PAC Ops™ |
| Programmable Output Formats | PAC, PAC64 and Wiegand |
| Maximum Read Range | 20mm |
| Intruder Grading | N/A |
| Environment | IP65 - Indoor/ Outdoor weather resistant |
| Power | 12 – 24V DC, <90 mA @ 12V DC |
| Operating Temperature | -40 to 66 oC |
| Operating Humidity | 10 to 85% Relative Humidity |
| Audio/Visual Indicators | Audible Sounder and Red/Green LEDs |
| Tamper Output | Yes, certified to EN 50131-1 and EN 50131-3 |
| Recommended Cabling | PAC output - 6 core 24 AWG alarm cable (unscreened) Wiegand output – 5 core 22 AWG cable |
| Material | UL rated Polycarbonate |
| Certification | CE compliant |
| Warranty | Lifetime against electronic failure |



Date of print/release: (September 2020)

This document is provided by STANLEY Security or its affiliates ("STANLEY") for general information purposes only. STANLEY warrant the accuracy of the data as at the date of print/release, but it may be subject to change after such date. STANLEY will not be responsible for any loss or damage that may arise from reliance thereof. Copyright © STANLEY Security 2020. PAC, GDX and 3xLOGIC are the trade marks of STANLEY Security, Stanley Black & Decker, Inc., or their affiliates.

Ordering Information:

PAC Access Control, 1 Park Gate Close,
 Bredbury, Stockport, Cheshire, SK6 2SZ
 customerservices@pacgdx.com | +44 (0) 161 406 3400
 www.pacgdx.com